

Product Description

Odorless defoaming agent STA-XA530 is an excellent defoaming and desoaming agent, shows effectiveness during in the production and processing of coating, especially suitable for epoxy resin systems and adhesives.

Typical Properties

Components	Solid content	Specified Gravity (g/ml)	Appearance	refractive index	Solvent
organosilicon polymer	5%	0.81	Colorless Tranparent viscous liquid	1.45	Hydrocarbon mixture

Features and advantages:

STA-XA530 is a highly potent defoaming agent and air release, suitable for solvent and solvent-free coating systems. It is manufactured and treated effectively and particularly recommended for epoxy systems

STA-XA530 is a perceived odorless product that can effectively avoid the solvent odor obsession for the workshop.

Application scope

suitable for Protective coating system, industrial coating, architectural coating wood and furniture coatings, , sealant, decoration parts glue.

Usage,

Recommended usage 0.3-0.8% of total fomulation, grinding before use.

Package:

25KG/barrel

Cautions:

Sealed and keep in cool space, do not contact with eye and skin directly, do not stain other products and container, please make a trial before put in production. Use before expired.

The data above are for experimental reference only and do not have any guarantee . Users should carry out test applicability according to their own conditions and requirements.

For any questions, please consult our technicians 0769-22364709 22364149 23037849 Fax: 22382985

Santol chemicals marketing headquarter address: Rm 606 Guojing Building, Nancheng CBD Headquarter base, Nancheng District, Dongguan City, Guangdong China